

Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group1 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER Absortech Absorpole, Absortop, Absorflex, Absorbag

Chemical name: Calcium chloride, CaCl₂

CAS-number: 10043-52-4 EC- number: 233-140-8

REACH- number: 01-2119494219-28

1.2 RELEVANT IDENTIFIED USES OF

THE SUBSTANCE OR MIXTURE

Use as a desiccant, absorbent

AND USES ADVISED AGAINST Formulation or re-packing

Use at industrial sites
Widespread use by professional workers

Consumer use

1.3 DETAILS OF THE SUPPLIER OF THE Absortech Group

SAFETY DATA SHEET

Tryckerivägen 4

311 44 Falkenberg, Sweden

info@absortech.com Phone: 034-64 20 70

1.4 EMERGENCY TELEPHONE

NUMBER

In emergency situations, contact National Poisons Information Service:

In England and Wales: NHS 111 - dial 111. In Scotland: NHS 24 - dial 111.

SECTION 2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE (CLP)

Health hazards:

The product is classified as hazardous to health.

Causes serious eye irritation. (Eye Irrit.2; H319).

Environmental hazards

The product is not classified as hazardous to the environment.

Physical hazards

The product is not classified for physical hazards.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group2 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

2.2 LABEL ELEMENTS

Hazard Pictograms



Signal word

WARNING

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/hearing protection.

P305+P351+ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

P338 to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Other information

Criteria for PBT and vPvB are not applicable for inorganic compounds (calcium chloride).

The substance does not meet the criteria for endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605.

2.3 OTHER HAZARDS

May form explosible dust-air mixture if dispersed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 SUBSTANCES

Substance EC No. CAS No. REACH No. Conc. Classification

w/w % (CLP)

Calcium chloride ^a 233-140-8 10043-52-4 01- 100% Eye Irrit. 2 H319

2119494219-28

a) Harmonised classification according to Annex VI, part 3, table 3.1 and 3.2, Regulation (EC) No 1272/2008 (CLP).

Other information

For a full text of H- phrases: See Section 16



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group3 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 4. FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

Inhalation

Fresh air and rest. If symptoms persist, call a physician.

Skin contact

Take off contaminated clothing. Wash skin immediately with soap and water. If symptoms persist, call a physician.

Eye contact

Rinse immediately with soft jet of water or eye wash for a few at least 15 minutes. Use temperate water. Keep eyelids apart, remove contact lenses. Consult a doctor if symptoms persist.

Ingestion

Rinse the mouth and drink water. Do not induce vomiting. Consult a doctor if symptoms persist.

Information to medical advice

No specific information.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Inhalation: May cause mild/transient irritation.

Skin Contact: May cause mild / transient irritation.

Eye Contact: Causes intense burning, tearing / increased lacrimation.

Ingestion: May cause irritation in the mouth and throat.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No information.

SECTION 5. FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Suitable extinguishing media: Use the same extinguishing media as recommended for the surroundings.

Unsuitable extinguishing media: None known

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Not combustible.

In case of fire, toxic and corrosive fumes such as hydrogen chloride and other combustion products may develop.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group4 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

5.3 ADVICE FOR FIREFIGHTERS

Precautions according to the standard procedure for chemical fires. Use breathing apparatus to protect against toxic / corrosive gases and suitable fire-resistant protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Avoid dust formation. Avoid contact with skin and eyes. Wear protective gloves, eye protection and protective clothing when cleaning and keep unprotected persons away.

6.2 ENVIRONMENTAL PRECAUTIONS

Prevent discharge to drains.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Sweep up and handle in accordance with local regulations.

6.4 REFERENCE TO OTHER SECTIONS

See Section 8 for Exposure controls / personal protection and Section 13 for disposal considerations.

SECTION 7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Avoid inhalation and direct contact with the product. Do not eat, drink and smoke when handling the product. Normal hand hygiene. May form explosible dust-air mixture if dispersed.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store in a cool dry place in a well-ventilated area. The product is hydroscopic. Store in the labeled original container. Suitable packaging materials are polyethylene, polypropylene and plastic materials such as PVDF, PTFE and PFA. Unsuitable packaging material: aluminum

7.3 SPECIFIC END USE

See Section 1.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group5 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure limits according to National regulations (Great Britain EH40, Workplace exposure limits (Fourth Edition 2020)

Contains no substances with occupational exposure limits in the work environment. This information refers to Great Britain. For other countries, refer to national legislation

Other information

Calcium chloride DNEL (worker):

Inhalation: 5 mg/m³ (local effect, long-term exposure) Inhalation: 10 mg/m³ (local effect, short-term exposure)

8.2 EXPOSURE CONTROLS

Appropriate technical measures

Methods are designed so that the concentration of dust is kept as low as possible by using closed processes, local point extraction or the like.

There should be a place for eye rinsing at the workplace.

Personal protection

Eye/face protection: Protective glasses shall be used.

Skin protection: At risk of direct contact protective gloves should be used.

Recommended glove material: PVC, neoprene and natural rubber.

Respiratory protection: When handling large amounts, respirators may be needed, according to EN

143. Particle filter: P2

Other protection: Long-sleeved coat / overalls and full-coverage shoes.

Thermal hazard. Not relevant.

8.3 ENVIRONMENTAL EXPOSURE CONTROLS

Prevent release to the environment.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group6 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Product description

Physical state: Solid / powder / granules

Colour White, grey (the substance could have small impurities of iron that gives

light nuance coloration to the end product depending on the state of

oxidation of iron itself (off-white, yellow, pink)).

Odour: Odourless

Melting-point / freezing-point: 782°C (101.3 kPa)

Boiling point or initial boiling point and

boiling range:

> 1600 °C

Lower and upper explosion limit: Not applicable Flashpoint: Not relevant Auto-ignition temperature: Not relevant Decomposition temperature: No data

pH: No data

Kinematic viscosity: Not relevant (solid)

Solubility: Soluble in water, 745 g/L (20°C)

Partition coefficient, n-octanol/water: Not relevant, as the substance decomposes in water (half-life less than 12

hours)

Vapour pressure:

Relative density:

Relative vapour density:

Particle characteristics:

Not relevant

No data

9.2 OTHER INFORMATION

-

9.2.1 INFORMATION WITH REGARD TO PHYSICAL HAZARD CLASSES

Explosive properties: Not explosive. Oxidising properties: Not oxidising. Flammability: Not flammable.

9.2.2 OTHER SAFETY CHARACTERISTICS

Not relevant



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group7 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 10. STABILITY AND REACTIVITY

10.1 REACTIVITY

The product is not reactive in normal handling and storage.

10.2 CHEMICAL STABILITY

The product is stable under normal handling and storage.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Calcium chloride can react violently with water.

10.4 CONDITIONS TO AVOID

Avoid exposing the substance to moisture during storage.

10.5 INCOMPATIBLE MATERIALS

The substance may react with strong oxidizing agents / reducing agents. In an aqueous solution, the substance may be corrosive to metals.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

No hazardous decomposition products known.

SECTION 11. TOXICOLOGICAL INFORMATION

The substance is classified as hazardous to the health (eye irritation). Specific effects are described below.

11.1 INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008

Acute toxicity: Not classified as acutely toxic.

Calcium chloride LD₅₀ Oral Rat: 2301 mg/kg

LD₅₀ Dermal Rabbit: >5000 mg/kg

Skin corrosion/irritation Not considered being corrosive / irritant to the skin, OECD 404.

Repeated and prolonged contact may appear dehydrating on the skin.

Serious eye damage / irritation: The product is irritating to the eyes, OECD 405.

Respiratory or skin sensitization: Not considered being sensitizing.

Germ cell mutagenicity: Not considered to cause mutations in germ cells.

Carcinogenicity Not considered to be carcinogenic.

Reproductive toxicity Not considered to be toxic to reproduction.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group8 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Specific organ toxicity - single exposure If inhaled, dust may be irritating to the upper respiratory tract and lungs.

(STOT):

Specific organ toxicity - repeated

exposure (STOT):

Not considered to cause damage to organs after repeated exposure.

Aspiration Hazard: Not relevant since the substance is not a liquid.

Specific effects

_

11.2 INFORMATION ON OTHER HAZARDS

Endocrine disrupting properties: The substance does not meet the criteria for endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605.

SECTION 12. ECOLOGICAL INFORMATION

The product is not classified as a hazardous to the environment and is not expected to result in any negative environmental consequences but should be handled according to good industrial standards.

12.1 TOXICITY

Calcium chloride LC₅₀ Fish 96h: 4630 mg/L (Pimephales promelas)

EC₅₀ Daphnia 48h: 2400 mg/L (Daphnia magna)

IC₅₀ Algae 72h:): >4000 mg/L (Pseudokirchneriella subcapitata)

12.2 PERSISTENCE AND DEGRADABILITY

For inorganic substances no degradation test needs to be performed.

However, calcium chloride is not expected to undergo photolysis or biodegradation.

12.3 BIOACCUMULATIVE POTENTIAL

Calcium chloride is easily dissociated into calcium and chloride ions and both ions are essential constituents of the body of all animals hence if a high amount would be taken up this is regulated by the body. Bioaccumulation of calcium chloride is consequently not expected.

12.4 MOBILITY IN SOIL

Calcium chloride is soluble in water and its vapor pressure is negligible.

Calcium chloride is not expected to be absorbed in soil due to its dissociation properties and high water solubility. As for the behaviour of calcium in soil, the calcium ion may bind to soil particulate or may form stable inorganic salts with sulphate and carbonate ions. The chloride ion is mobile in soil and eventually drains into surface water because it is readily dissolved in water.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group9 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

12.5 RESULTS OF PBT AND vPvB ASSESSMENT

The criteria for PBT and vPvB are not applicable to inorganic substances (calcium chloride).

12.6 ENDOCRINE DISRUPTING PROPERTIES

The substance does not meet the criteria for endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605.

12.7 OTHER ADVERSE EFFECTS

None known.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Product

Dispose of contents/container to approved waste disposal facility in accordance with local regulations. Prevent discharge into drains, watercourses etc.

Packaging

Well emptied packaging can be treated as conventional waste and be left for incineration (energy recovery). Emptied and cleaned packaging can be treated as conventional waste and be left for recycling. EWC- code: 15 01 02 (Plastic packaging)



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group10 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

SECTION 14. TRANSPORTINFORMATION

This product is not covered by the regulations for transportation of dangerous goods.

	ADR/RID	ADN	IMDG	IATA
14.1 UN NUMBER OR ID NUMBER	N/A	N/A	N/A	N/A
14.2 UN PROPER SHIPPING NAME	N/A	N/A	N/A	N/A
14.3 TRANSPORT HAZARD CLASS	N/A	N/A	N/A	N/A
14.4 PACKING GROUP	N/A	N/A	N/A	N/A
14.5 ENVIRONMENTAL HAZARDS	N/A	N/A	N/A	N/A

14.6 SPECIAL PRECAUTIONS FOR USER

Not relevant.

14.7 MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS

Not relevant.

SECTION 15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

This safety data sheet is prepared in accordance with the EUROPEAN PARLIAMENT AND COUNCIL REGULATION (EC) No 1907/2006 of 18 December 2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH) and Commission Regulation (EU) No 2020/878 of 18 June 2020 amending the European Parliament and Council Regulation (EC) No 1907/2006 on the registration, evaluation, authorization and restriction of chemicals (REACH).

Regulations

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substance and mixtures (CLP).

Great Britain EH40, Workplace exposure limits (Fourth Edition 2020), Occupational Exposure Limits, UK.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 replacing Annex III to Directive 2008/98/EC of the European Parliament and of the Council on waste.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group11 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Other information

The product does not contain any substances listed in REACH Annex XIV (Authorization List) or on the EU Candidate List of Substances with Substances of Very High Concern (SVHC) in concentrations $\geq 0.1\%$ (w / w).

The product is not affected by any restrictions under REACH, Annex XVII.

15.2 CHEMICAL SAFETY ASSESSMENT

A Chemical Safety Assessment has been carried out for calcium chloride.

SECTION 16. OTHER INFORMATION

Classification procedure

Test data is prioritized when classifying the product. When no test data are available, the classification rules in regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures (CLP) been used.

Hazard statements in Section 3

H319 Causes serious eye irritation.

Abbreviations

ADN	International	Carriage of	Dangerous (Goods by I	nland Waterways	
-----	---------------	-------------	-------------	------------	-----------------	--

ADR International Carriage of Dangerous Goods by Road

BCF Bio Concentration Factor

EC₅₀ Effective Concentration (concentration that gives response in 50 % of test subjects)

ECHA European Chemical Agency
EmS Emergency Schedule Information

IARC International Agency for Research on Cancer

IC₅₀ Inhibitory Concentration (concentration that shows inhibition in 50 % of the test subjects)

IATA Dangerous goods regulation / ICAO Technical Instructions for the Safe Transport of Dangerous Goods

ICAO by Air

IMDG International Maritime Dangerous Goods Code

LC50 Lethal Concentration (concentration causing the death of 50 % of a group of test animals)

LD₅₀ Lethal Dose (dose causing the death of 50 % of a group of test animals)

LDLo Lethal Dose Low (= Lowest dose of a toxic material at which the death of the exposed test animal occurs.

Log Pow Partition coefficient octanol - water
PBT Persistent Bio-accumulative and Toxic

RID International Carriage of Dangerous Goods by Rail

STEL Short Term Exposure Limit
SVHC Substance of Very High Concern
TWA Time-weighted average

vPvB very Persistent and very Bioaccumulative



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group12 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Advice about education

The user of this product should have training that is relevant to the properties of the product and relevant use.

References

- 1) Registered substances, ECHA.
- 2) Chemical substances online, Prevent.
- 3) Information from the supplier

Version description

The information has been modified under the following sections in the safety data sheet: 2, 7, 9, 11, 12, 14, 15, 16. The safety data sheet is dated 2023-04-20 and it replaces version dated 2021-03-18.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group13 of 52

EXPOS	EXPOSURE SCENARIO FOR CALCIUM CHLORIDE		
No.	Short title		
ES 1	Formulation or re-packing		
ES 2	Use at industrial sites; Various sectors (SU 1, SU 2a, SU 2b, SU 4, SU 5, SU 6b, SU 8, SU 9, SU 11, SU 12, SU 13, SU 14, SU 15, SU 16, SU 17)		
ES 3	Widespread use by professional workers; Various sectors (SU 0, SU 1, SU 13, SU 19, SU 20)		
ES 4	Widespread use by professional workers; Various sectors (SU 0, SU 1, SU 5, SU 13, SU 19, SU 20)		
ES 5	Consumer use; PC 0, 2		



Revision date Replaces First edition Art. no Issued by Page 2023-04-20 2021-03-18 2013-02-19 Absortech Group 14 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

ES 1: Formulation or re-packing

Title section

ES name: Formulation or re-packing; Distribution of substance	
Environment	
1: Formulation into mixture	ERC 2
Worker	
2: Chemical production in closed process without likelihood of exposure or in containment conditions.	PROC 1
3: Chemical production in closed continuous process with occasional controlled exposure.	PROC 2
4: Formulation in closed batch processes with occasional controlled exposure.	PROC 3
5: Chemical production where opportunity for exposure arises	PROC 4
6: Mixing or blending in batch processes	PROC 5
7: Transfer of a substance or mixture during process sampling at dedicated facilities	PROC 8b, PROC 26
8: Transfer of a substance or mixture during process sampling at non-dedicated facilities	PROC 8a, PROC 26
9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC 9, PROC 26
10: Use as laboratory reagent	PROC 15, PROC 26
11: Tabletting, compression, extrusion, pelettisation, granulation	PROC 14
12: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC 8a, PROC 26
13: Transfer of substance or mixture (charging/discharging) at dedicated-facilities	PROC 8b, PROC 26
14: Equipment cleaning and maintenance at non-dedicated facility	PROC 8a, PROC 28
15: Manual maintenance (cleaning and repair) of machinery	PROC 28



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group15 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Conditions of use affecting exposure

Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product	article)	characteristics
FIOUUCL	ai ucie	Cilaracteristics

Covers concentrations up to 100 %

Solid, medium dustiness. Covers also liquid form

Technical and organisational conditions and measures

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.

Use suitable eye protection.

Other conditions affecting workers exposure

Indoor use

Assumes process temperature up to 20 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Chemical production in closed process without likelihood of exposure or in containment conditions. (PROC 1)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Chemical production in closed continuous process with occasional controlled exposure. (PROC 2)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour).



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group16 of 52

Formulation in closed batch processes with occasional controlled exposure. (PROC 3)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Chemical production where opportunity for exposure arises (PROC 4)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a
Mixing or blending in batch	minimum of 5-10 air changes per air can be applied. Covers use up to 8 h/day
processes (PROC 5)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Transfer of a substance or mixture during process sampling at dedicated facilities (PROC 8b, PROC 26)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Transfer of a substance or mixture during process sampling at non-dedicated facilities (PROC 8a, PROC 26)	Covers use up to 1 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC 9, PROC 26)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Use as laboratory reagent (PROC 15, PROC 26)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Tabletting, compression, extrusion, pelettisation, granulation (PROC 14)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour).



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2023-04-20
 2021-03-18
 2013-02-19
 Absortech Group
 17 of 52

Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC 8a, PROC 26)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Transfer of substance or mixture (charging/discharging) at dedicated-facilities (PROC 8b, PROC 26)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Equipment cleaning and maintenance at non-dedicated facility (PROC 8a, PROC 28)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52] Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Manual maintenance (cleaning and repair) of machinery (PROC 28)	Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52] Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group18 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Exposure estimation and reference to its source

Worker exposure: Chemical production in closed process without likelihood of exposure or in containment conditions. (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.01 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.04 mg/m³ (TRA Workers 3.0)	< 0.01

Worker exposure: Chemical production in closed continuous process with occasional controlled exposure. (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Formulation in closed batch processes with occasional controlled exposure. (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Chemical production where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Mixing or blending in batch processes (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group19 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Transfer of a substance or mixture during process sampling at dedicated facilities (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Transfer of a substance or mixture during process sampling at non-dedicated facilities (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.1 mg/m³ (TRA Workers 3.0)	0.02
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC 9, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Use as laboratory reagent (PROC 15, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC 14)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14



Revision dateReplacesFirst editionArt. noIssued byPage2023-04-202021-03-182013-02-19-Absortech Group20 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated-facilities (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Equipment cleaning and maintenance at non-dedicated facility (PROC 8a, PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Manual maintenance (cleaning and repair) of machinery (PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (PROC 8a estimate used to cover PROC 28)	0.1
Inhalation, local, acute	2 mg/m³ (PROC 8a estimate used to cover PROC 28)	0.2



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 21 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

ES 2: Use at industrial sites; Various sectors (SU 1, SU 2a, SU 2b, SU 4, SU 5, SU 6b, SU 8, SU 9, SU 11, SU 12, SU 13, SU 14, SU 15, SU 16, SU 17)

Title section

ES name: Use at industrial site (e.g. Industrial Indoor use as Process aid, Industrial Outdoor use)

Sector of use: Agriculture, forestry, fishery (SU 1), Mining (without offshore industries) (SU 2a), Offshore industries (SU 2b), Manufacture of food products (SU 4), Manufacture of textiles, leather, fur (SU 5), Manufacture of pulp, paper and paper products (SU 6b), Manufacture of bulk, large scale chemicals (including petroleum products) (SU 8), Manufacture of fine chemicals (SU 9), Manufacture of rubber products (SU 11), Manufacture of plastics products, including compounding and conversion (SU 12), Manufacture of other non-metallic mineral products, e.g. plasters, cement (SU 13), Manufacture of basic metals, including alloys (SU 14), Manufacture of fabricated metal products, except machinery and equipment (SU 15), Manufacture of computer, electronic and optical products, electrical equipment (SU 16), General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment. (SU 17)

machinery, equipment, venicles, other transport equipment. (50-17)	
Environment	
1: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	ERC 4
Worker	
2: Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions	PROC 1
3: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC 2
4: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC 3
5: Chemical production where opportunity for exposure arises	PROC 4
6: Mixing or blending in batch processes	PROC 5
7: Calendering operations	PROC 6



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 22 of 52

8: Transfer of a substance or mixture during process sampling at non-dedicated facilities with a local exhaust ventilation	PROC 8a, PROC 26
9: Transfer of a substance or mixture during process sampling at non-dedicated facilities without a local exhaust ventilation	PROC 8a, PROC 26
10: Transfer of a substance or mixture during process sampling at dedicated facilities with a local exhaust ventilation	PROC 8b, PROC 26
11: Transfer of a substance or mixture during process sampling at dedicated facilities without a local exhaust ventilation	PROC 8b, PROC 26
12: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities with a local exhaust ventilation.	PROC 8a, PROC 26
13: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities without a local exhaust ventilation.	PROC 8a, PROC 26
14: Transfer of substance or mixture (charging/discharging) at dedicated facilities with a local exhaust ventilation.	PROC 8b, PROC 26
15: Transfer of substance or mixture (charging/discharging) at dedicated facilities without a local exhaust ventilation.	PROC 8b, PROC 26
16: Equipment cleaning and maintenance at non-dedicated facility	PROC 8a, PROC 28
17: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) at facilities with a local exhaust ventilation	PROC 9, PROC 26, PROC 27b
18: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) at facilities without a local exhaust ventilation	PROC 9, PROC 26
25: Tabletting, compression, extrusion, pelettisation, granulation	PROC 14
26: Use as laboratory reagent	PROC 15, PROC 26, PROC 27b
27: Open processing and transfer operations at substantially elevated temperature (=< melting point - Medium fugacity)	PROC 23, PROC 27a
28: Open processing and transfer operations at substantially elevated temperature (> melting point - High fugacity)	PROC 23, PROC 27a
29: Manual maintenance (cleaning and repair) of machinery at noon-dedicated facilities	PROC 28



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 23 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Conditions of use affecting exposure

Control of worker exposure

Conditions of use applicable to all contributing scenarios

Technical and organisational conditions and measures

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.

Use suitable eye protection.

Other conditions affecting workers exposure

Assumes process temperature up to 20 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions (PROC 1)	Covers concentrations up to 100 % Solid, medium dustiness. Covers also liquid form Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Indoor use
Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)	Covers concentrations up to 100 % Solid, medium dustiness. Covers also liquid form Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Indoor use
Manufacture or formulation in closed batch processes with occasional controlled exposure	Covers concentrations up to 100 % Solid, medium dustiness. Covers also liquid form



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 24 of 52

or processes with equivalent	Covers use up to 8 h/day
containment condition (PROC 3)	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
,	Indoor use
Chemical production where opportunity for exposure	Covers concentrations up to 100 %
arises (PROC 4)	Solid, medium dustiness. Covers also liquid form
	Covers use up to 8 h/day
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %
	Indoor use
Mixing or blending in batch	Covers concentrations up to 100 %
processes (PROC 5)	Solid, medium dustiness. Covers also liquid form
	Covers use up to 8 h/day
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
	Outdoor use
Calendering operations (PROC	Covers concentrations up to 100 %
6)	Solid, medium dustiness. Covers also liquid form
	Covers use up to 8 h/day
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
	Indoor use
Transfer of a substance or	Covers concentrations up to 100 %
mixture during process	Solid, medium dustiness. Covers also liquid form
sampling at non-dedicated facilities with a local exhaust	Covers use up to 1 h/day
ventilation (PROC 8a, PROC 26)	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 25 of 52

Transfer of a substance or mixture during process	Covers concentrations up to 100 %
sampling at non-dedicated facilities without a local	Solid, medium dustiness. Covers also liquid form
	Covers use up to 1 h/day
exhaust ventilation (PROC 8a, PROC 26)	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
,	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
	Indoor use
Transfer of a substance or	Covers concentrations up to 100 %
mixture during process sampling at dedicated facilities	Solid, medium dustiness. Covers also liquid form
with a local exhaust	Covers use up to 8 h/day
ventilation (PROC 8b, PROC 26)	Local exhaust ventilation; Inhalation - minimum efficiency of 95 %
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use
Transfer of a substance or	Covers concentrations up to 100 %
mixture during process	Solid, medium dustiness. Covers also liquid form
sampling at dedicated facilities without a local exhaust	Covers use up to 8 h/day
ventilation (PROC 8b, PROC 26)	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at non-dedicated facilities with	Solid, medium dustiness. Covers also liquid form
a local exhaust ventilation.	Covers use up to 8 h/day
(PROC 8a, PROC 26)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %
	Indoor use
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging)	Solid, medium dustiness. Covers also liquid form
at non-dedicated facilities without a local exhaust	Covers use up to 8 h/day
ventilation. (PROC 8a, PROC 26)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).



26 of 52

Revision date Replaces First edition Art. no Issued by Page

2013-02-19

2021-03-18

2020-10-02

F	
	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
	Indoor or outdoor use
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at dedicated facilities with a	Solid, medium dustiness. Covers also liquid form
local exhaust ventilation.	Covers use up to 8 h/day
(PROC 8b, PROC 26)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 95 %
	Indoor use
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at dedicated facilities without	Solid, medium dustiness. Covers also liquid form
a local exhaust ventilation.	Covers use up to 8 h/day
(PROC 8b, PROC 26)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Indoor or outdoor use
Equipment cleaning and	Covers concentrations up to 100 %
maintenance at non-dedicated facility (PROC 8a, PROC 28)	Solid, medium dustiness. Covers also liquid form
Julinty (FROC 88, FROC 28)	Covers use up to 8 h/day
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %
	Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52]
	Indoor use
Transfer of substance or	Covers concentrations up to 100 %
mixture into small containers (dedicated filling line, including	Solid, medium dustiness. Covers also liquid form
weighing) at facilities with a	Covers use up to 8 h/day
local exhaust ventilation (PROC 9, PROC 26, PROC 27b)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 27 of 52

	Indoor use
mixture into small containers	Covers concentrations up to 100 %
	Solid, medium dustiness. Covers also liquid form
(dedicated filling line, including weighing) at facilities without	Covers use up to 8 h/day
a local exhaust ventilation (PROC 9, PROC 26)	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
(PROC 9, PROC 20)	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
	Indoor or outdoor use
Tabletting, compression,	Covers concentrations up to 100 %
extrusion, pelettisation, granulation (PROC 14)	Solid, medium dustiness. Covers also liquid form
grandiation (FROC 14)	Covers use up to 8 h/day
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use
Use as laboratory reagent	Covers concentrations up to 100 %
(PROC 15, PROC 26, PROC 27b)	Solid, medium dustiness. Covers also liquid form
	Covers use up to 8 h/day
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use
Open processing and transfer	Covers concentrations up to 100 %
operations at substantially elevated temperature (=<	Solid, medium dustiness. Covers also liquid form
melting point - Medium	Covers use up to 8 h/day
fugacity) (PROC 23, PROC 27a)	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Indoor use
Open processing and transfer	Covers concentrations up to 100 %
operations at substantially elevated temperature (>	Solid, medium dustiness. Covers also liquid form
melting point - High fugacity)	Covers use up to 8 h/day
(PROC 23, PROC 27a)	Provide a good standard of controlled ventilation (5 to 10 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 90 %



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 28 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

	Indoor use
and repair) of machinery at noon-dedicated facilities (PROC 28)	Covers concentrations up to 100 % Solid, medium dustiness. Covers also liquid form Covers use up to 8 h/day Provide a basic standard of general ventilation (1 to 3 air changes per hour). Local exhaust ventilation; Inhalation - minimum efficiency of % Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via
	enclosed lines [E52] Indoor use

Exposure estimation and reference to its source

Worker exposure: Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.01 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.04 mg/m³ (TRA Workers 3.0)	< 0.01

Worker exposure: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 29 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Chemical production where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Mixing or blending in batch processes (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Calendering operations (PROC 6)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of a substance or mixture during process sampling at non-dedicated facilities with a local exhaust ventilation (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.1 mg/m³ (TRA Workers 3.0)	0.02
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Transfer of a substance or mixture during process sampling at non-dedicated facilities without a local exhaust ventilation (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.1 mg/m³ (TRA Workers 3.0)	0.02
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Transfer of a substance or mixture during process sampling at dedicated facilities with a local exhaust ventilation (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.05 mg/m³ (TRA Workers 3.0)	0.01
Inhalation, local, acute	0.2 mg/m³ (TRA Workers 3.0)	0.02



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 30 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Transfer of a substance or mixture during process sampling at dedicated facilities without a local exhaust ventilation (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities with a local exhaust ventilation. (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities without a local exhaust ventilation. (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities with a local exhaust ventilation. (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.035 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.14 mg/m³ (TRA Workers 3.0)	0.014

Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities without a local exhaust ventilation. (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Equipment cleaning and maintenance at non-dedicated facility (PROC 8a, PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 31 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) at facilities with a local exhaust ventilation (PROC 9, PROC 26, PROC 27b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) at facilities without a local exhaust ventilation (PROC 9, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC 14)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Use as laboratory reagent (PROC 15, PROC 26, PROC 27b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (TRA Workers 3.0)	0.1
Inhalation, local, acute	2 mg/m³ (TRA Workers 3.0)	0.2

Worker exposure: Open processing and transfer operations at substantially elevated temperature (=< melting point - Medium fugacity) (PROC 23, PROC 27a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 32 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Open processing and transfer operations at substantially elevated temperature (> melting point - High fugacity) (PROC 23, PROC 27a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.03 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.12 mg/m³ (TRA Workers 3.0)	0.012

Worker exposure: Manual maintenance (cleaning and repair) of machinery at noon-dedicated facilities (PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.5 mg/m³ (ECETOC TRA Workers)	0.1
Inhalation, local, acute	2 mg/m³ (ECETOC TRA Workers)	0.2

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Scaling tool: For the evaluation of spraying activities the ART (Advanced Reach Tool) modeling tool has been used. In case the DU cannot demonstrate safe use with the conditions currently presented in this SDS Annex, the ART modeling Tool can be used as scaling tool.



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 33 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

ES 3: Widespread use by professional workers; Various sectors (SU 0, SU 1, SU 13, SU 19, SU 20)

Title section

ES name: Professional use; Indoor use

Sector of use: Other (SU 0), Agriculture, forestry, fishery (SU 1), Manufacture of other non-metallic mineral products, e.g. plasters, cement (SU 13), Building and construction work (SU 19), Health services (SU 20)

Environment	
1: Indoor use; Professional use	ERC 8a
Worker	
2: Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions	PROC 1
3: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC 2
4: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC 3
5: Chemical production where opportunity for exposure arises	PROC 4
6: Mixing or blending in batch processes	PROC 5
7: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities	PROC 8a, PROC 26
8: Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC 8b, PROC 26
9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC 9, PROC 26
10: Use as laboratory reagent	PROC 15, PROC 26



Revision date Replaces First edition Art. no Issued by Page 2021-03-18 2020-10-02 2013-02-19 34 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

11: Manual activities involving hand contact PROC 19

12: Use of functional fluids in small devices PROC 20

13: Equipment cleaning and maintenance at non-dedicated facility PROC 8a, PROC 28

14: Manual maintenance (cleaning and repair) of machinery at non-dedicated facility PROC 28

Conditions of use affecting exposure

Control of worker exposure

Conditions of use applicable to all contributing scenarios

Conditions and measures related to personal protection, hygiene and health evaluation	
Use suitable eye protection.	
Other conditions affecting workers exposure	
Indoor use	
Assumes process temperature up to 20 °C	

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions (PROC 1)	Covers concentrations up to 100 % Solid, medium dustiness Covers use up to 8 h/day Assumes a good basic standard of occupational hygiene is implemented Provide a basic standard of general ventilation (1 to 3 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Chemical production in closed continuous process with occasional controlled exposure	Covers concentrations up to 100 % Solid, medium dustiness



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 35 of 52

or processes with equivalent containment conditions (PROC	Covers use up to 8 h/day
2)	Assumes a good basic standard of occupational hygiene is implemented
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Manufacture or formulation in	Covers concentrations up to 100 %
closed batch processes with occasional controlled exposure	Solid, medium dustiness
or processes with equivalent	Covers use up to 8 h/day
containment condition (PROC 3)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Chemical production where	Covers concentrations up to 100 %
opportunity for exposure arises (PROC 4)	Solid, medium dustiness
arises (FROC 4)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Mixing or blending in batch	Covers concentrations up to 100 %
processes (PROC 5)	Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 36 of 52

	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at non-dedicated facilities	Solid, medium dustiness
(PROC 8a, PROC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging)	Solid, medium dustiness
at dedicated facilities (PROC 8b, PROC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Transfer of substance or	Covers concentrations up to 100 %
mixture into small containers (dedicated filling line, including	Solid, medium dustiness
weighing) (PROC 9, PROC 26)	Covers use up to 8 h/day



37 of 52

Revision date Replaces First edition Art. no Issued by Page

2013-02-19

2021-03-18

2020-10-02

	Assumes a good basic standard of occupational hygiene is implemented
	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Use as laboratory reagent	Covers concentrations up to 100 %
(PROC 15, PROC 26)	Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Manual activities involving	Covers concentrations up to 100 %
hand contact (PROC 19)	Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of 80 %
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Use of functional fluids in small	Covers concentrations up to 100 %
devices (PROC 20)	Solid, medium dustiness
	55.14)54.4 445555



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 38 of 52

	Assumes a good basic standard of occupational hygiene is implemented
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Equipment cleaning and	Covers concentrations up to 100 %
maintenance at non-dedicated facility (PROC 8a, PROC 28)	Solid, medium dustiness
Julinity (1 NOC 64, 1 NOC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
	Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52]
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Respiratory protection (APF of 10) is to be worn in those case where there is potential for peak exposure. Alternatively, good general ventilation with a minimum of 5-10 air changes per air can be applied.
Manual maintenance (cleaning	Covers concentrations up to 100 %
and repair) of machinery at non-dedicated facility (PROC	Solid, medium dustiness
28)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Provide a basic standard of general ventilation (1 to 3 air changes per hour).
	Local exhaust ventilation; Inhalation - minimum efficiency of %
	Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52]
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 39 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

other parts of the body, then these body parts should also be protected
with impervious garments in a manner equivalent to those described for
the hands.; For further specification, refer to section 8 of the SDS.

Exposure estimation and reference to its source

Worker exposure: Chemical production in closed process without likelihood of exposure or in containment conditions or processes with equivalent containment conditions (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.01 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.04 mg/m³ (TRA Workers 3.0)	< 0.01

Worker exposure: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Chemical production where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28



Revision date Replaces First edition Art. no Issued by Page

2021-03-18 2020-10-02 2013-02-19 - 40 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Mixing or blending in batch processes (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1.4 mg/m³ (TRA Workers 3.0)	0.28
Inhalation, local, acute	5.6 mg/m³ (TRA Workers 3.0)	0.56

Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC 9, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Use as laboratory reagent (PROC 15, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Manual activities involving hand contact (PROC 19)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 41 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Use of functional fluids in small devices (PROC 20)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	1 mg/m³ (TRA Workers 3.0)	0.2
Inhalation, local, acute	4 mg/m³ (TRA Workers 3.0)	0.4

Worker exposure: Equipment cleaning and maintenance at non-dedicated facility (PROC 8a, PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Manual maintenance (cleaning and repair) of machinery at non-dedicated facility (PROC 28)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (ECETOC TRA Workers)	0.14
Inhalation, local, acute	2.8 mg/m³ (ECETOC TRA Workers)	0.28

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Scaling tool: For the evaluation of spraying activities the ART (Advanced Reach Tool) modeling tool has been used. In case the DU cannot demonstrate safe use with the conditions currently presented in this SDS Annex, the ART modeling Tool can be used as scaling tool.



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	_		42 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

ES 4: Widespread use by professional workers; Various sectors (SU 0, SU 1, SU 5, SU 13, SU 19, SU 20)

Title section

ES name: Professional use; Outdoor use

Sector of use: Other (SU 0), Agriculture, forestry, fishery (SU 1), Manufacture of textiles, leather, fur (SU 5), Manufacture of other non-metallic mineral products, e.g. plasters, cement (SU 13), Building and construction work (SU 19), Health services (SU 20)

137) Health 321 (1863 (30 20)	
Environment	
1: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)	ERC 8d
Worker	
2: Chemical production in closed process without likelihood of exposure or in containment conditions.	PROC 1
3: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC 2
4: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions	PROC 3
5: Chemical production where opportunity for exposure arises	PROC 4
6: Mixing or blending in batch processes	PROC 5
7: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities	PROC 8a, PROC 26
8: Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC 8b, PROC 26
9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC 9, PROC 26



Revision date	Replaces	First edition	Art. no	Issued by	Page	
2021-03-18	2020-10-02	2013-02-19	-		43 of 52	

Absortech Absorpole, Absortop, Absorflex, Absorbag

10: Use as laboratory reagent	PROC 15, PROC 26
11: Mixing operations; Manual activities involving hand contact	PROC 19
12: Equipment cleaning and maintenance at non-dedicated facility	PROC 8a
13: Use of functional fluids in small devices	PROC 20

Conditions of use affecting exposure

Control of worker exposure

Conditions of use applicable to all contributing scenarios

Other conditions affe	ting workers exposure
Outdoor use	
Assumes process tem	erature up to 20 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Chemical production in closed process without likelihood of exposure or in containment conditions. (PROC 1)	Covers concentrations up to 100 % Solid, medium dustiness Covers use up to 8 h/day Assumes a good basic standard of occupational hygiene is implemented Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Use suitable eye protection
Chemical production in closed	Covers concentrations up to 100 %



Revision date	Replaces	First edition	Art. no	Issued by	Page	
2021-03-18	2020-10-02	2013-02-19	-		44 of 52	

continuous process with occasional controlled exposure	Solid, medium dustiness
or processes with equivalent	Covers use up to 8 h/day
containment conditions (PROC 2)	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
Manufacture or formulation in	Covers concentrations up to 100 %
closed batch processes with occasional controlled exposure	Solid, medium dustiness
or processes with equivalent	Covers use up to 8 h/day
containment conditions (PROC 3)	Assumes a good basic standard of occupational hygiene is implemented
<i>5</i> ,	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
Chemical production where opportunity for exposure arises (PROC 4)	Covers concentrations up to 100 % Solid, medium dustiness Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
Mixing or blending in batch	Covers concentrations up to 100 %



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	-		45 of 52

	T
processes (PROC 5)	Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at non-dedicated facilities	Solid, medium dustiness
(PROC 8a, PROC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
Transfer of substance or	Covers concentrations up to 100 %
mixture (charging/discharging) at dedicated facilities (PROC	Solid, medium dustiness
8b, PROC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.



Revision date	Replaces	First edition	Art. no	Issued by	Page	
2021-03-18	2020-10-02	2013-02-19	-		46 of 52	

	Use suitable eye protection
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
Transfer of substance or	Covers concentrations up to 100 %
mixture into small containers (dedicated filling line, including	Solid, medium dustiness
weighing) (PROC 9, PROC 26)	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Use suitable eye protection
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
Use as laboratory reagent (PROC 15, PROC 26)	Covers concentrations up to 100 % Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	-		47 of 52

Г	
Mixing operations; Manual	Covers concentrations up to 100 %
activities involving hand contact (PROC 19)	Solid, medium dustiness
,	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
Equipment cleaning and	Covers concentrations up to 100 %
maintenance at non-dedicated facility (PROC 8a)	Solid, medium dustiness
Julius (i ii e e e e e e e e e e e e e e e e e	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Handle substance within a closed system [ES47] Drain down and flush system prior to equipment break-in or maintenance [E55] Transfer via enclosed lines [E52]
	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
	Use suitable eye protection
	Wear suitable respiratory protection.; Inhalation - minimum efficiency of 90 %; For further specification, refer to section 8 of the SDS.
Use of functional fluids in small	Covers concentrations up to 100 %
devices (PROC 20)	Solid, medium dustiness
	Covers use up to 8 h/day
	Assumes a good basic standard of occupational hygiene is implemented
	Wear chemically resistant gloves (tested to EN374) in combination with



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	_		48 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Use suitable eye protection

Exposure estimation and reference to its source

Worker exposure: Chemical production in closed process without likelihood of exposure or in containment conditions. (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	7E-3 mg/m³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.028 mg/m³ (TRA Workers 3.0)	< 0.01

Worker exposure: Chemical production in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Manufacture or formulation in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Chemical production where opportunity for exposure arises (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	-		49 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Worker exposure: Mixing or blending in batch processes (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of substance or mixture (charging/discharging) at non-dedicated facilities (PROC 8a, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC 8b, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC 9, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Use as laboratory reagent (PROC 15, PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Mixing operations; Manual activities involving hand contact (PROC 19)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.35 mg/m³ (TRA Workers 3.0)	0.07



Revision date	Replaces	First edition	Art. no	Issued by	Page
2021-03-18	2020-10-02	2013-02-19	-		50 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, acute	1.4 mg/m³ (TRA Workers 3.0)	0.14

Worker exposure: Equipment cleaning and maintenance at non-dedicated facility (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Worker exposure: Use of functional fluids in small devices (PROC 20)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	0.7 mg/m³ (TRA Workers 3.0)	0.14
Inhalation, local, acute	2.8 mg/m³ (TRA Workers 3.0)	0.28

Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: Application of de-icing agent (mixture of 70% NaCl and 30% of a 20% solution of CaCl2) assumes a fraction of 0.06 of CaCl2 in road salt with an annual tonnage of 0.09 tonnes/km for 25 emission days per year. Application of de-icing agent (liquid CaCl2 brine (max. 35% solution)) assumes a fraction of 0.35 of CaCl2 in road salt with an annual tonnage of 0.28 tonnes/km for 25 emission days per year. Application of Dust suppressor (solid CaCl2 (up to 80%)) assumes a fraction of 0.8 of CaCl2 in road salt with an annual tonnage of 2.4 tonnes/km for 3 emission days per year. Application of Dust suppressor (solid CaCl2 (up to 37%)) assumes a fraction of 0.37 of CaCl2 in road salt with an annual tonnage of 1.11 tonnes/km for 3 emission days per year.



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 51 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

ES 5: Consumer use; PC 0, 2

Title section

ES name: Consumer use; Indoor or outdoor use

Product category: Adsorbents (PC 2)

Environment	
1: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC 8a
2: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)	ERC 8d
Consumer	
3: Humidity adsorbants	PC 0
4: Adsorbents	PC 2

Conditions of use affecting exposure

Control of consumer exposure: Humidity adsorbants (PC 0)

Product (article) characteristics
Covers concentrations up to 100 %
Solid, medium dustiness. Covers also liquid form
Amount used (or contained in articles), frequency and duration of use/exposure
Covers use up to 1 events per day
Covers use up to 24 h
Information and behavioral advice for consumers
Requires room with good ventilation
Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Other conditions affecting consumers exposure



 Revision date
 Replaces
 First edition
 Art. no
 Issued by
 Page

 2021-03-18
 2020-10-02
 2013-02-19
 52 of 52

Absortech Absorpole, Absortop, Absorflex, Absorbag

Release area <= 125 m2

Control of consumer exposure: Adsorbents (PC 2)

Product (article) characteristics

Covers concentrations up to 100 %

Solid, medium dustiness. Covers also liquid form

Amount used (or contained in articles), frequency and duration of use/exposure

Covers use up to 1 events per day

Covers use up to 24 h

Information and behavioral advice for consumers

Requires room with good ventilation

Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.

Other conditions affecting consumers exposure

Release area <= 125 m2

Exposure estimation and reference to its source

Consumer exposure: Humidity adsorbants (PC 0)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	5E-3 mg/m³ (ConsExpo)	< 0.01
Inhalation, local, acute	0.01 mg/m³ (ConsExpo)	< 0.01

Consumer exposure: Adsorbents (PC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, local, long term	5E-3 mg/m³ (ConsExpo)	< 0.01
Inhalation, local, acute	0.01 mg/m³ (ConsExpo)	< 0.01